



7-1/4" Hypoid Saw

Model No:5377MG

Hypoid gear system provides increased transmission of power

- Factory greased packed, no oil required
- 0° - 51.5° bevel cutting capacity is ideal for truss and rafters
- New magnesium diecast for base plate, blade case and motor housing
- Ergonomic top and rear handle with rubberized grip for operator comfort and control
- Ideal for Framers, Home Builders, Masons, and Contractors
- High quality, heat treated hypoid steel gears do not wear like bronze-alloy worm drive gears



STANDARD EQUIPMENT

INCLUDED:

7-1/4" Carbide tipped saw blade (A-94530)
Hex wrench 6 (783204-6)

SPECIFICATIONS

Blade diameter	7-1/4" (185 mm)
Max cutting capacities:	
90°	2-3/8" (60 mm)
45°	1-3/4" (44 mm)
50°	1- 9/16" (40 mm)
No load speed	4,500 RPM
AMPS (120 V)	15.0
Overall length	17-3/4" (450 mm)
Net weight	13 lbs. (5.9 kg)
Shipping weight	16.0 lbs. (7.2 kg))

Available at:



Superprem
Your Stone Tool Source!

Superprem.com

StoneToolSource.com

1-866-808-3838

Specifications subject to change without notice. All rights reserved.