



# UNIBLACK1 *Eliminate defect of Black Granite*

We suggest UNIBLACK 1 for eliminating the defects of black granites like black africa or black impala and similar material. Its application brings to an darkening the surface of the material making it blackest and more homogeneous on the surface, more black. Quick drying.



# UNIBLACK2 *Increases the black effect*

It is a black liquid wax used to increase the black effect on polished, brushed and smooth surfaces. The UNIBLACK2 increase the black effect without the increase of the gloss. It is used on black materials as black zimbawe, black Africa and black Indian granite. The product can be used on proper automatic waxing machine or manually. It is suggested to restore old materials which has lost the blackness.



## Instructions for use

The product must be evenly applied on dry and clean materials. The presence of water, dust or dirt may effect the uniformity of the surface. We suggest spreading the product using a brush or cloth. Let the wax dry completely, only a few minutes. Carefully buff the surface with a clean cloth or felt. The excess must be removed after the application. You will obtain an immediate effect . It is possible to apply by automatic waxing line. The product freezes at 0 / +1°C. It returns to liquid once at room temperature. Close can tightly after each use

## Shelf life :

The products will last at least 2 years in the normal condition between 18-25°C, kept away from source of heat, humidity and sun light .

## Quantity to be used:

Depends a lot from the stone. Normally with 1 liter is possibile to treat 20-30 square meters of stone. The consume depends a lot from the porosity of the material.



Available at:

**Superprem**  
Your Stone Tool Source!

[Superprem.com](http://Superprem.com)

[StoneToolSource.com](http://StoneToolSource.com)

1-866-808-3838

Specifications subject to change without notice. All rights reserved.